

CUTTING EDGE IN LEAK TESTING TECHNOLOGY



POWER. PERFORMANCE. SPEED.

OUR STORY

The best businesses are formed when people provide a creative solution to an existing problem. In 2005, Barry Money and Greg Rider realized that the manufacturing industry was in need of an extremely fast and repeatable air leak testing system. LeakMaster was formed to provide a solution to that need. In 2006, they began developing and refining the first generation of LeakMaster air leak testing instruments and, over the past decade, have continued to refine their instruments by incorporating the latest technological advances and digital innovations. Today, LeakMaster is considered an industry leader in providing non-destructive leak testing equipment to the global marketplace. LeakMaster air leak testers and automated leak testing systems have become invaluable to those in the Automotive and Heavy Equipment industries as well as in the testing of Engines, Drive Trains, Off road and ATV components, Consumer Products and Medical Devices.





LeakMaster Ultraflow V3 POWER. PERFORMANCE. SPEED.

MODERN CONNECTIVITY PROVEN SOLUTIONS TOTAL CONTROL

EtherNet/IP[®] RS-232

You just can't test slow, with UltraFlow. The UltraFlow is LeakMaster's latest mass flow leak testing innovation specifically designed to reduce cycle time and improve repeatability. When your application requires extremely fast cycle times, we're confident in saying UltraFlow is the fastest, most repeatable way to leak test...period! **The UltraFlow is ideal for quickly testing large parts yet versatile enough to test small parts.** Optional Ethernet/IP module for seamless integration with Allen Bradley EtherNet/IP or other compatible devices, eliminates I/O wiring, reduces start-up time and hardware cost. Provides ultimate control and the ability to capture valuable leak rate data for data collection systems, critical for today's production environment.

STILL THE FASTEST & PACKED WITH NEW CAPABILITIES!



PROGRAMMABLE ELECTRONIC PRESSURE REGULATOR NEW AND IMPROVED **EtherNet/IP**^{*} FEATURING "SLAVE MODE" DIGITAL MASS FLOW SENSOR WITH BROAD TESTING RANGE NEW PRESSURE DECAY MODE FOR MICRO LEAK DETECTION LED STATUS INDICATOR DUAL ACCESS DOORS FOR FLEXIBLE MOUNTING

CAPABLE OF TESTING LEAKS FROM 1 SCCM TO 300 SLPM MAKING IT VERSATILE FOR A VARIETY OF APPLICATIONS



RUN SCREEN

- The large, touchscreen display makes leak testing effortless.
- All pass/fail and in-process information are clearly displayed for easy viewing.

	San Program		nster	
	PROGRAM TIM	ERS/SEC	TEST LIMITS	TEST TYPE
	PRETEST DELAY	O SEC	MIN. PRESS 25.000	
	FILL TIME	4 SEC	MAX. PRESS 32.000	KPM PROGRAM PROGRAM NAME
۵	STAB TIME	4 SEC		
	TEST TIME	7 SEC	GAL DATA	UNIT SELECT
	VENT TIME	3 SEC	COMP: 0.05 CAL. STATUS:	SELECT OUTPUTS
			LEAK ORIFICE: 172	SEPN PRESSURE SETPOINT: 28.9935 KM Set Pressure
	ស	🔓 Adm	in 00000	⊃ ⊣

SET UP SCREEN

- The easy to understand layout reduces set -up time, builds confidence, and eliminates confusion.
- The intuitive design gives unparalleled control, without multiple set-up screens.
- All leak timers and limits are clearly presented in their proper order.

		RESULTS		Lea	aki	las	ster				
	2018-01-03 08:54:07	0.583 SCCM	3.922 PSIG	CALIBRATION	-10.000 SCCM	500.000 SOCM	0.05476	3	Decay Tube	隐	
	2018-01-03 08:25:35	411.679 SCCM	3.699 PS8G	CALIBRATION	-10.000 SCCM	500.000 SCCM	0.054429	3	Decay Tube	ゐ	
	2018-01-03 00:25:18	0.000 SCCM	0.000 PSIG	TEST STOWED	-10.000 SCCM	300.000 SOCM	0.054420	3	Decay Tube	16	1
	2018-01-02 14:23:03	425.346 SCCM	3.515 P58G	PASS	+10.000 SCCM	500.000 SCCM	0.054429	3	Decay Tube	16	
1	2018-01-02 14:22:39	-5.144 SCCM	3.898 PSIG	PASS	-10.000 SCEM	500.000 SCCM	0.054420	3	Decay Tube	16	N
4	2018-01-02 14:22:06	0.425 SLPM	24.393 KPA	PASS	-0.010 SLPM	0.500 SLPM	0.37521269117760003	3	Decay Tube	麀	1
	2018-01-02 14:21:44	-0.001 SLPM	26.870 KPA	PASS	-0.010 SLPM	6.500 SLPM	0.37521269117760003	3	Decay Tube	16	
	2018-01-02 14:21:08	0.426 SLPM	3.490 PSIG	PASS	-0.010 SLPM	0.500 SLPM	0.054420	3	Decay Tube	隐	
	2018-01-02 14:20:67	430.406 SCCM	3.501 958G	PASS	-10.000 SCCM	500.000 SOCM	0.054429	3	Decay Tube	16	
	2018-01-02 14:19:31	-9.364 SCCM	3.896 PSIG	PASS	-10.000 SCCM	500.000 SCCM	0.054420	3	Decay Tube	16	
	2018-01-02	-0.008	3,891		-0.010	0.500			Decas	-	×

RESULTS SCREEN

- Built-in data collection with auto save for proven, effective data collection; without hassle.
- The information is saved as a CSV file for viewing in Microsoft Excel or other text viewers.

FEATURE	STANDARD	OPTIONAL
PROGRAMS PER CHANNEL	999	
# OF CHANNELS	1	
MASS FLOW SENSOR	0-200 SLPM	0-250 sccm, 0-750 sccm, 0-10 SLPM, 0-50 SLPM, 0-100 SLPM, 0-200 SLPM, 0-300 SLPM
INPUTS	(16) 24VDC PNP	
OUTPUTS	(16) 24VDC PNP	
COMMUNICATIONS	DIGITAL IO	ETHERNET IP®, PROFINET , RS-232
DATA COLLECTION	USB FLASH, FTP	MasterCloud™
PRESSURE RANGE	0-15 PSIG	



TECHNICAL SPECIFICATIONS



Finally, a mass flow tester, with the power and versatility to test a huge variety of components such as:

EXHAUST COMPONENTS INTAKE MANIFOLDS OIL PANS AUTOMOTIVE LIGHTING ASSEMBLIES, & MORE

The programmable electronic pressure regulator allows the user to have multiple pressure set points for each independent program, which enables the UltraFlow to be used for multiple applications without operator intervention.

Remote network connectivity allows LeakMaster to quickly support any tester in the field, and the new optional WIFI module makes network connectivity even easier.

Subscribe to **MasterCloud**[™], an exclusive LeakMaster cloud based data storage, that provides easy access to previous result information at any time.

LEARN MORE AT: LEAKMASTERUSA.COM

